

W-BS тип S з шестигранною головою



Тип	Довжина анкера l [мм]	Товщина кріплення			Оцинкована сталь	Нержавіюча сталь A4	Діаметр бура d ₀ [мм]	Глибина отвору h ₂ [мм]	Момент затягування T _{inst} ≤ [Нм]	Розмір ключа [мм]	Діаметр голови [мм]	Уп., шт
		h _{ef,1}	h _{ef,2}	h _{ef,3}	t _x [мм]	Артикул №						
W-BS 5 *	40	5	-	-		5929125005	-	5	45	8	SW10	12,5
	50	15	-	-		5929125015	-		55			
	60	25	-	-		5929125025	-		65			
W-BS 6 *	40	-	-	-		5929126005	-	6	45	10	SW13	15
	50	10	-	-		5929126015	5929226015		55			
	60	20	5	-		5929126025	5929226025		65			
	80	40	25	-		5929126045	-		85			
	100	60	45	-		5929126065	-		105			
W-BS 8	50	5	-	-		5929128005	-	8	60	20	SW13	16
	60	15	5	-		5929128015	-		70			
	70	25	15	5		5929128025	5929228025		80			
	80	35	25	15		5929128035	5929228035		90			
	90	45	35	25		5929128045	-		100			
	100	55	45	35		5929128055	-		110			
	120	75	65	55		5929128075	-		130			
	140	95	85	75		5929128095	-		150			
	160	115	105	95		5929128115	-		170			
W-BS 10	60	5	-	-		5929121005	-	10	70	40	SW15	20
	80	25	5	-		5929121025	-		90			
	90	35	15	5		5929121035	5929221035		100			
	100	45	25	15		5929121045	5929221045		110			
	120	65	45	35		5929121065	5929221065		130			
	140	85	65	55		5929121085	-		150			
	160	105	85	75		5929121105	-		170			
W-BS 12	80	15	-	-		5929122015	-	12	90	60	SW17	23
	110	45	25	10		5929122045	-		120			
W-BS 14	80	5	-	-		5929124005	-	14	90	80	SW21	28
	110	35	10	-		5929124035	-		120			
	130	55	30	15		5929124055	-		140			

W-BS тип S з шестигранною головою та збільшеною шайбою



W-BS 10	180	125	105	95	5929121125	-	10	190	40	SW15	44	25
	200	145	125	115	5929121145	-		210				15
	240	185	165	155	5929121185	-		250				
	280	225	205	195	5929121225	-		290				
	320	265	245	235	5929121265	-		330				